



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

## EAGLE G4C

SUPER PREMIUM SYNTHETIC  
MOTORCYCLE ENGINE  
LUBRICANT

American Synthol, Inc.

4343 Shallowford Road, Suite D2,  
Marietta, GA 30062  
Phone: 888-378-9290  
Fax: 888-731-9534

## AMERILUBE EAGLE G4C

AMERILUBE EAGLE G4C is a super premium synthetic lubricant designed specifically for 4 cycle motorcycle engines. EAGLE G4C gives excellent clutch control in oil flooded clutch type units. It provides outstanding service in reducing wear, providing protection under severe and high temperature conditions and in improving horsepower and reducing both fuel consumption and emissions. Amerilube EG4C exceeds the requirements of virtually every manufacturer in the world including Harley Davidson, Honda, Yamaha, Kawaski, BMW, and Suzuki.

- Outstanding Oxidation Stability
  - Outstanding Thermal Stability
  - Outstanding Shear Stability
  - Outstanding Wear Reduction
  - Extended Lubricant Life
- Outstanding Deposit Control
  - Friction Reduction
  - Very Low Volatility
  - Improved Fuel Economy
  - Reduced Oil Consumption

## Typical Properties

Lubricant Designation	ASTM Test Method	5W30	5W40	10W50
SAE Viscosity	-	5W30	5W40	10W50
Viscosity Index	D2270	175	173	176
Vis cSt @ 40 °C	D445	49.1	73.7	105
Vis cSt @ 100 °C	D445	9.3	12.7	16.9
Vis SUS @ 100 °F	D445	229.0	342.0	486.6
Vis SUS @ 212 °F	D445	56.4	69.0	85.6
Pour Point °F	D97	-60	-54	-51
Flash Point °F	D92	422	428	430
Cold Crank Viscosity cP @ -20 °C (-4 °F)	D2602	-	-	3150
Cold Crank Viscosity cP @ -30 °C (-22 °F)	D2602	2500	3100	-
Borderline Pumping Temp, °C (°F)	D38294	-43 (-45)	-35 (-31)	-30 (-22)
TBN	D2896	11	11	11
Sulfated Ash, %WT	D874	1.0	1.0	1.0