



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SBLX

**SUPER PREMIUM SYNTHETIC
BEARING FLUID**

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE SBLX

AMERILUBE SYNTHETIC BEARING LUBRICANT

AMERILUBE SYNTHETIC BEARING LUBRICANTS are premium, synthetic products using an advanced technology additive system and special synthetic friction modified base fluids. SBLX is specifically designed for heavy-duty, high temperature applications in dryer steam drum bearings at elevated temperatures. They give excellent service in all types of roll mill bearings.

AMERILUBE SYNTHETIC BEARING LUBRICANTS give outstanding service in even the most demanding applications.

- Excellent Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Excellent Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Very Long Fluid Life
- Excellent Rust Control
- Excellent Sludge and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Water Separation

Typical Properties

Lubricant Designation	SBLX-100	SBLX-150	SBLX-220	SBLX-320	SBLX-460	SBLX-680
Viscosity Index	120	141	165	169	180	189
Viscosity cSt @ 40 °C	101.0	135.0	209.1	305.2	420.0	620.1
Viscosity cSt @ 100 °C	12.7	17.4	27.0	36.6	49.5	69.2
Viscosity SUS @ 100 °F	-	-	-	-	-	-
Viscosity SUS @ 212 °F	-	-	-	-	-	-
Flash Point °F	510	515	520	522	525	523
Auto-Ignition Point °F	795	801	804	810	812	815
Pour Point °F	-48	-46	-45	-31	-22	-18
Timken "OK" Load Kg	40	40	40	40	40	40
Copper Corrosion, 24 Hr	1a	1a	1a	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0	40/40/02	40/40/0	40/40/0	40/40/0