



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SFG

SUPER PREMIUM SYNTHETIC
COMPRESSOR FLUIDS



American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE SFG - FOOD GRADE

AMERILUBE SFG - SYNTHETIC FOOD GRADE compressor lubricants are high performance fluids that are approved by the USDA for H-1 applications (lubricants with incidental food contact). They fully comply with the requirements of FDA 21 CFR 178.3570.

AMERILUBE SFG's provide excellent service and are designed for extended drain intervals.

- Excellent Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Very Long Life Fluid
- Energy Savings
- Carbon and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Excellent Materials Compatibility
- Reduced Lubricant Consumption
- Excellent Rust & Corrosion Control

Typical Properties

Lubricant Designation	SFG100	SFG200	SFG250	SFG300
NSF H1 Registration Number	133898	133896	-	133897
Viscosity Index	110	106	106	107
Viscosity cSt @ 40 °C	38.2	46.8	67.5	101.0
Viscosity cSt @ 100 °C	5.7	7.0	8.9	11.9
Viscosity SUS @ 100 °F	178.6	218	313	469.9
Viscosity SUS @ 212 °F	44.9	49.1	55.6	65.6
Flash Point °F	430	445	465	510
Auto-Ignition Point °F	710	720	745	800
Pour Point °F	-45	-38	-35	-32
Four Ball, 40 Kg, 1200 RPM, 167°F				
1 Hr, Scar Dia mm	.40	.40	.40	.40
Four Ball Weld Point, Kg	100	100	100	110
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0	40/40/0	40/40/0