



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SGL-AUTO

SUPER PREMIUM SYNTHETIC
GEAR LUBRICANT

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE SYNTHETIC AUTOMOTIVE GEAR LUBRICANTS

AMERILUBE SYNTHETIC AUTOMOTIVE GEAR LUBRICANTS are super premium, synthetic products using American Synthol's advanced technology additive system and special synthetic friction modified base fluids. They are designed for extremely heavy duty service and give outstanding service in even the most demanding applications.

AMERILUBE SYNTHETIC AUTOMOTIVE GEAR LUBRICANTS meet and exceed the performance requirements for : API, GL-5, & MT1, Rockwell Int'l (0-76-e), MIL-PRF-2105E, Spicer Axle Mack GO-G/S GOJ+ , Limited Slip Differentials, & Eaton AXLED1UPS-109, and are recommended for any application calling for automotive extreme pressure gear lubricants.

- Excellent Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto Ignition Points
- Excellent Shock Loading Performance
- Excellent Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Very Long Fluid Life
- Excellent Rust Control
- Excellent Sludge and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Water Separation

Typical Properties

Lubricant Designation	SGL 75W90	SGL 80W140
Viscosity Index	142	173
Vis cSt @ 40 °C	131.0	260.0
Vis cSt @ 100 °C	17.1	33.2
Vis SUS @ 100 °F	-	-
Vis SUS @ 212 °F	-	-
Flash Point °F	510	515
Auto-Ignition Point °F	839	839
Pour Point °F	-40	-35
Timken "OK" Load Lb.	40	40
Copper Corrosion, 24 Hr.	1b	1b
Demulsibility, 130 °F, 30 min	40/38/2	40/38/2