



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS



American Synthol, Inc.

2930 Mountain Trace  
Roswell, GA 30075  
Phone: 800-633-5457  
Fax: 888-731-9534

## AMERILUBE SERIES SGLX

### AMERILUBE SYNTHETIC GEAR LUBRICANT

AMERILUBE SYNTHETIC GEAR LUBRICANTS are premium, Synthetic Products using an advanced technology additive system and special synthetic friction modified base fluids. Proven in countless millions of horsepower hours of service in almost every type of gear application.

AMERILUBE SYNTHETIC GEAR LUBRICANTS give outstanding service in even the most demanding applications.

- Excellent Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Excellent Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Very Long Fluid Life
- Excellent Rust Control
- Excellent Sludge and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Water Separation

### Typical Properties

Lubricant Designation	SGLX-100	SGLX-150	SGLX-220	SGLX-320	SGLX-460	SGLX-680	SGLX-1000
Viscosity Index	120	141	165	169	180	189	140
Viscosity cSt @ 40 °C	101.0	135.0	209.1	305.2	420.0	620.1	937
Viscosity cSt @ 100 °C	12.7	17.4	27.0	36.6	49.5	69.2	68
Viscosity SUS @ 100 °F	-	-	-	-	-	-	-
Viscosity SUS @ 212 °F	-	-	-	-	-	-	-
Flash Point °F	510	515	520	522	525	523	520
Auto-Ignition Point °F	795	801	804	810	812	815	794
Pour Point °F	-48	-46	-45	-31	-22	-18	-15
Timken "OK" Load Kg	40	40	40	40	40	40	40
Copper Corrosion, 24 Hr	1a	1a	1a	1a	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0