



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS



American Synthol, Inc.

4343 Shallowford Road, Suite D2,  
Marietta, GA 30062  
Phone: 888-378-9290  
Fax: 888-731-9534

## SHCL - HIGH TEMP CHAIN LUBRICANT

AMERILUBE SHCL - HIGHTEMP CHAIN LUBRICANT is a super premium, synthetic lubricant specifically designed to lubricate chains under severe high temperature service.

AMERILUBE SHCL is particularly well suited to applications where temperatures exceed 400 °F.

AMERILUBE SHCL provides outstanding service, even in the most severe food plant operating

- Outstanding Oxidation Stability
  - Very High Viscosity Index
  - Very High Flash & Auto-Ignition Points
  - Very Low Volatility
  - Extremely High Film Strength
  - Excellent Carbon Control
  - Excellent Materials Compatibility
- Very Tenacious and Long Lasting
  - Excellent Rust Control
  - Excellent Lubricity
  - Energy Savings
  - Reduced Maintenance Costs
  - Reduced Downtime
  - Reduced Lubricant Consumption

## Typical Properties

Lubricant Designation	SHCL 320	SHCL 460
Viscosity Index	131	138
Vis cSt @ 40 °C	318.2	450.2
Vis cSt @ 100 °C	30.2	40.5
Vis SUS @ 100 °F	-	-
Vis SUS @ 212 °F	-	-
Flash Point °F	468	470
Auto-Ignition Point °F	756	760
Pour Point °F	-22	-18
Four Ball, 40 Kg, 1200 RPM, 167 °F 1		
Hr, Scar DIA mm	.40	.40
Four Ball Weld Point, Kg	100	100
Copper Corrosion, 24 Hr.	1a	1a
Demulsibility, 130 °F, 30 min	40/38/2	40/38/2