



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

## SEWING MACHINE OIL

SUPER PREMIUM SYNTHETIC FLUID

American Synthol, Inc.

4343 Shallowford Road, Suite D2,  
Marietta, GA 30062  
Phone: 888-378-9290  
Fax: 888-731-9534

## SEWING MACHINE OIL

AMERILUBE - SEWING MACHINE OIL is a super premium, synthetic fluid with an advanced technology additive system. It is blended from the finest materials available and has been proven in countless hours of service in virtually every type of equipment. It is odorless and NON-STAINING.

AMERILUBE - SEWING MACHINE OIL gives outstanding service, even in the most severe operating conditions.

- Outstanding Oxidation Stability
- High Viscosity Index
- High Flash & Auto Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Long Fluid Life
- Excellent Rust Control
- Carbon & Varnish Control
- Energy Savings
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Reduced Misting

## Typical Properties

Lubricant Designation	SEWING MACHINE OIL
Viscosity Index	121
Viscosity cSt @ 40 °C	13
Viscosity cSt @ 100 °C	3.2
Viscosity SUS @ 100 °F	69.45
Viscosity SUS @ 212 °F	36.85
Flash Point °F	320
Auto-Ignition Point °F	610
Pour Point °F	-20
Four Ball, 40 Kg, 1200 RPM, 167°F 1 Hr, Scar Dia mm	.48
Four Ball Weld Point, Kg	60
Copper Corrosion, 24 Hr	1a
Demulsibility, 130 °F, 30 min	40/40/0